



Consistent, repeatable results

The HydroPro™ Plus initiates a new generation of professional sous vide immersion circulators. Featuring Sous Vide Toolbox™, an intuitive on-board guided cooking experience that simplifies sous vide cooking by using scientific algorithms to calculate time to temperature and pasteurization for a vast range of foods.

The HydroPro™ Plus includes a digital needle probe that displays the core temperature of the food in real-time, enabling delta cooking. Data is stored on-board and can be transferred to the HACCP Manager App via Bluetooth for easy logging of all your sous vide cooks.

Programming and repeatability of your cooks is made simple thanks to 'My Presets' and usability has been enhanced via a large touch screen that allows easy manual input of cooking parameters. The powerful heater and newly designed pumping system ensure precise temperature control across a wide range of cooking volumes.

Designed with food safety and simple maintenance in mind, the design features a smooth waterproof construction, quick-release clamp, and a magnetic impeller for easy cleaning and descaling. Removable parts are commercial dishwasher safe.

The HydroPro Plus cvs750 240v Sous Vide Immersion Circulator

Technical Specifications – PERFORMANCE

| | |
|---------------------|--------------|
| Power | 1485 Watts |
| Flow Rate | 17 L/Min |
| Max Water Bath Size | 45L with lid |

DURABILITY

- IPX7 Water Resistant
- NSF and IEC Commercially Certified
- Stainless Steel Exterior
- Ruby Bearing
- Tungsten Carbide Shaft



PRECISION

| | |
|---------------------------|---------------|
| Temperature Resolution | 0.1°F/0.1°C |
| Temperature Stability | ± 0.1°F/0.1°C |
| Maximum Water Temperature | 194°F/90°C |

USABILITY

| | |
|---|--------------------------------|
| Color TFT Touch Display | 360° Adjustable Flow Direction |
| On-board Cooking Guide Sous Vide Toolbox™ | Coil-less Heating Chamber |
| Manual Time & Temperature Controls | Low Water Detection |
| Integrated Digital Probe | Magnetic Impeller Coupling |
| Variable Flow Speed | Adjustable & Detachable Clamp |

CONNECTIVITY

Bluetooth

WEIGHTS & DIMENSIONS

| | |
|---------------------------------|--|
| Unit Weight | 4.4lb / 2kg |
| Unit Dimensions (L x D x H) | 14.6in x 3.7in x 6.7in / 37.1cm x 9.3 x 17cm |
| Shipping Weight | 7.1lb / 3.2kg |
| Shipping Dimensions (L x D x H) | 16.3in x 5.8in x 9.9in / 41.5cm x 14.7cm x 25.2cm |
| SKU Number | CSV750PSS4JAN1 Australia/New Zealand CSV750PSS4GHK1 Hong Kong CSV750PSS4EAN1 South Korea |

ACCESSORIES

- Adjustable & Detachable Clamp
- Magnetic Impeller
- 360° Adjustable Flow Direction Foot
- Digital Probe & Calibration Holder
- Carry Case with Handle.