



### Consistent, repeatable results

The HydroPro™ Plus initiates a new generation of professional sous vide immersion circulators. Featuring Sous Vide Toolbox™, an intuitive on-board guided cooking experience that simplifies sous vide cooking by using scientific algorithms to calculate time to temperature and pasteurization for a vast range of foods.

The HydroPro™ Plus includes a digital needle probe that displays the core temperature of the food in real-time, enabling delta cooking. Data is stored on-board and can be transferred to the HACCP Manager App via Bluetooth for easy logging of all your sous vide cooks.

Programming and repeatability of your cooks is made simple thanks to 'My Presets' and usability has been enhanced via a large touch screen that allows easy manual input of cooking parameters. The powerful heater and newly designed pumping system ensure precise temperature control across a wide range of cooking volumes.

Designed with food safety and simple maintenance in mind, the design features a smooth waterproof construction, quick-release clamp, and a magnetic impeller for easy cleaning and descaling. Removable parts are commercial dishwasher safe.

## The HydroPro Plus cvs750 240v Sous Vide Immersion Circulator

### Technical Specifications – PERFORMANCE

Power	1485 Watts
Flow Rate	17 L/Min
Max Water Bath Size	45L with lid

### DURABILITY

- IPX7 Water Resistant
- NSF and IEC Commercially Certified
- Stainless Steel Exterior
- Ruby Bearing
- Tungsten Carbide Shaft



### PRECISION

Temperature Resolution	0.1°F/0.1°C
Temperature Stability	± 0.1°F/0.1°C
Maximum Water Temperature	194°F/90°C

### USABILITY

Color TFT Touch Display	360° Adjustable Flow Direction
On-board Cooking Guide Sous Vide Toolbox™	Coil-less Heating Chamber
Manual Time & Temperature Controls	Low Water Detection
Integrated Digital Probe	Magnetic Impeller Coupling
Variable Flow Speed	Adjustable & Detachable Clamp

### CONNECTIVITY

Bluetooth

### WEIGHTS & DIMENSIONS

Unit Weight	4.4lb / 2kg
Unit Dimensions (L x D x H)	14.6in x 3.7in x 6.7in / 37.1cm x 9.3 x 17cm
Shipping Weight	7.1lb / 3.2kg
Shipping Dimensions (L x D x H)	16.3in x 5.8in x 9.9in / 41.5cm x 14.7cm x 25.2cm
SKU Number	CSV750PSS4JAN1 Australia/New Zealand CSV750PSS4GHK1 Hong Kong CSV750PSS4EAN1 South Korea

### ACCESSORIES

Adjustable & Detachable Clamp  
Magnetic Impeller  
360° Adjustable Flow Direction Foot  
Digital Probe & Calibration Holder  
Carry Case with Handle.